

Combi steamer Silversteam P-5230D



- ▶ Combi steamer Silversteam P
 - ✓ High power
 - ✓ Up to 5 x GN 2/3



- ▶ Rack control
 - ✓ To enable the selection of a program for each shelf
- ▶ The benefits of the Silversteam series
 - ✓ Faster heating and reheating times
 - ✓ Up to 30% reduction in cooking times
 - ✓ Ideal for cooking spaces used to full capacity

Description

More efficiency and greater time savings with the combi steamer Silversteam P 5 x GN 2/3 thanks to added extra power. Thanks to the high power and the rack control function, the cooking spaces can be used to full capacity. Reduced cooking times, faster heating times, and easy handling speak for themselves.

Features

- Power load: 4,8 kW | 400 V | 50 Hz
- Equipment connection: 3 NAC
- Temperature range: 50 °C to 300 °C
- Control unit: Touch
- Functions: Circulating air
Steam
Combi-steaming
Low temperature cooking
Delta-T cooking
Reversing motor direction (fan wheels)
Steam production by means of direct injection
- Rack control: Yes
- Continuous operation: Yes
- Vapour extractor: Yes
- Core temperature sensor connection: Side
- USB connection: Side
- Fan speed: 3 levels



- ▶ Electronic control with 600 programs (300 preinstalled, 300 programmable); up to 9 cooking phases per program



- ▶ Double door glazing, inner door can be opened easily for cleaning

▶ Continue on the next page

Combi steamer Silversteam P-5230D



- Type of drawers: Crosswise
- Number of drawers: 5
- Distance between trays: 74 mm
- Water connection: 3/4"
- Time adjustment: 0 to 599 minutes
- Number of fans: 1
- LED display: Steaming
Delta-T cooking
Cooking phases
Core temperature
Fan speed
Program
Temperature
Time
- Available on request: -
- Control lamp: -
- Series: Silversteam
- Temperature control: Stepless
- Interior lighting: Yes
- Format drawers: 2/3 GN
- Operating mode: Electro
- With cleaning system: No
- Material: CNS 18/10
- Important information: From a water hardness of 5° dH upwards, we urgently recommend fitting a suitable water softener and a water pressure of maximum 3 bar
- Material cooking chamber: CNS 18/10
- Including: 1 grid 2/3 GN
1 tray 2/3 GN
1 water supply hose
- Number of cooking phases: 9
- Number of cooking programs: 300 pre-installed programs
300 configurable programs
- Properties: Rounded baking chamber
Bearing rails can be detached
Double-winged door pane
LED lighting in door
Faster heating and reheating times
Up to 30 % reduction in cooking times
Ideal for cooking spaces used to full capacity
- Size: W 620 x D 775 x H 675 mm
- Weight: 58.6 kg

Combi steamer Silversteam P-5230D

Add on Products

Base unit Silversteam 230

CNS



- Material: Chrome-nickel steel
- Designed for: 2/3 GN combi-steamers Silversteam2 series
2/3 GN combi-steamers Silversteam series
- Important information: -
- Colour: Silver
- Base shelf: Yes
- Height-adjustable feet: No

Code-No. 115075
GTIN 4015613610641

Pump set f. combi steamer



- Material: Plastic
Metal
- Important information: -

Code-No. 116011
GTIN 4015613595146

GN container, 2/3, D65

CNS
18/10



- Content: 5,5 litre(s)
- Stackable: Yes
- Design: No perforation
- Reinforced edge: No
- Properties: -
- Surface: High-gloss
- Depth container: 65 mm

Code-No. A125065
GTIN 4015613271217

GN container, 2/3, D100

CNS
18/10



- Content: 9 litre(s)
- Stackable: Yes
- Design: No perforation
- Reinforced edge: No
- Properties: -
- Surface: High-gloss
- Depth container: 100 mm

Code-No. A125100
GTIN 4015613271224

Combi steamer Silversteam P-5230D

Add on Products

GN container, 2/3, D65, perforated

CNS
18/10



- Content: 5,5 litre(s)
- Stackable: Yes
- Design: With perforation (holes)
- Reinforced edge: No
- Properties: -
- Surface: High-gloss
- Depth container: 65 mm

Code-No. A103065
GTIN 4015613278940

Smoker-Box 1160



STAINLESS
STEEL



- Material: Stainless steel
- Model: With heating coil
- Designed for: Combined steamer
- Important information: Maximum smoking temperature: 200 °C
- Comprising: Mains adapter
Smoker-Box
- Volume: 1,16 litre(s)

Code-No. 117712
GTIN 4015613779195

Core temperature sensor set 1KA

STAINLESS
STEEL



- Designed for: Combi steamers series Silversteam
- Material temperature sensor: Stainless steel
- Important information: -
- Number of measuring points: 1
- Length cable: 1,8 m
- Set comprises: 1 core temperature sensor
1 holder

Code-No. 116009
GTIN 4015613595139

Hand shower f. combi steamer



- Length hose: 2 m
- Properties: Shutoff valve for fixed connection to water supply 1/2"
- Including: 1 holder
- Important information: -
- Water connection: 1/2"

Code-No. 116005
GTIN 4015613587189

Combi steamer Silversteam P-5230D

Add on Products

Perforated tray 2/3-AL



- Diameter perforation: 3 mm
- Gastronorm: 2/3 GN
- Edge: 4 sides, cover
- Silicone coating: No
- Material thickness: 1,5 mm
- Perforation: Yes
- Temperature resistant to: 260 °C

Code-No. 100417
GTIN 4015613734729

Perforated tray 2/3-SI



- Diameter perforation: 3 mm
- Gastronorm: 2/3 GN
- Edge: 4 sides, cover
- Silicone coating: Yes
- Material thickness: 1,5 mm
- Perforation: Yes
- Temperature resistant to: 260 °C

Code-No. 100425
GTIN 4015613734736

Oven gloves 420



- Properties: With flame protection
With hanger
Fabric density: 640 g/m²
- Material: Cotton 100 % (exterior)
- Colour: Black
- Important information: Do not wash to maintain flame protection
- Can be washed: No

Code-No. A500512
GTIN 4015613735481

Power cleaner F1L



- Order quantity unit: 1 box (6 bottles)
- Content: 6 x 1 litre
- Model: Liquid
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes

Code-No. 173278
GTIN 401561373346

Combi steamer Silversteam P-5230D

Add on Products

Intensive power cleaner F1L



- Order quantity unit: 1 box (6 bottles)
- Content: 6 x 1 litre
- Model: Liquid
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes

Code-No. 173280
GTIN 4015613773353

Combi steamer cleaner RS-5L



- Order quantity unit: 1 canister
- Designed for: Combi steamers with an automatic dosing system
- Ph level: 14
- HACCP compliant: No
- Chlorine-free: Yes
- Phosphate-free: No

Code-No. 116299V
GTIN 4015613813042

Pressure regulator



- Material: Brass
Chrome-plated
- Important information: -
- Water pressure: 1 - 6 bar (preset to 3 bar)
- Connection: 3/4"
- Operating temperature max.: 65 °C
- Incoming pressure max.: 16 bar

Code-No. 533051
GTIN 4015613468617