

## Vacuum packaging machine K 250/150L



- ▶ Functions: Combined vacuuming and sealing
- ▶ Vacuum pump: 150 L/min. (approx. 8/9 m<sup>3</sup>/h)
- ▶ Number of sealing seams: 1
- ✓ Sealing rod length: 250 mm



- ▶ Sealing duration can be regulated: 6 levels



- ▶ 2 insert plates
- ✓ For height compensation in the chamber

### Description

Powerful and solid chamber vacuum machine with intuitive control. Enclosed insert plates achieve height compensation in the chamber as required.

### Features

- Material lid: Plexiglas
- Power load: 0,5 kW | 230 V | 50 Hz
- Control unit: Toggle
- Control lamp: Combined vacuuming and sealing
- Digital display: ON/OFF
- Lighting: No
- ON/OFF switch: No
- Colour: Yes
- Number of welded joints: Silver
- Properties: 1
- Functions: -
- Material: Combined vacuuming and sealing
- Important information: Stainless steel
- Chamber dimensions: Plastic
- Length welding rod: -
- Length welding rod: W 256 x D 370 x H 125 mm
- Length welding rod: 250 mm

▶ Continue on the next page

## Vacuum packaging machine K 250/150L

- Vacuum pump: 150 L / min. (8-9 m<sup>3</sup> / hours)
- Vacuum control: -
- Vacuuming intensity can be regulated: No
- Including: 2 insert plates for height compensation (250 x 300 x 17 mm)
- Welding duration can be regulated: 6 levels
- Maximum vacuum: -995 mbar
- Size: W 320 x D 540 x H 265 mm
- Weight: 29 kg



## Vacuum packaging machine K 250/150L

### Add on Products

#### Vacuum bags K1,2L



- Content: 1,2 litre(s)
- Order quantity unit: 1 pack (100 bags)
- Important information: -
- Bag size: 160 x 250 mm
- Film thickness: 90 µM
- Designed for: Chamber vacuuming units
- Design: Smooth

Code-No. 300311  
GTIN 4015613729237

#### Vacuum sealer roll set 220



- Set comprises: 2 vacuum film rolls
- Width roll: 22 cm
- Important information: -
- Length roll: 5 m
- Film thickness: 80 µM
- Sous-Vide suitable: Yes
- Size: W 220 x D 40 x H 40 mm

Code-No. 300418  
GTIN 4015613728506