

WALL MOUNTED UNIT LUKE 1.9

€3,950.00

SKU:

7550.0115

Introducing the powerful Wall Mounted Unit Luke 1.9 – the ideal refrigeration solution for larger supermarkets and professional display environments!



The Wall Mounted Unit Luke 1.9 is a powerful and stylish refrigeration solution for professionally presenting chilled products. This freestanding model in black finish offers increased capacity and is ideal for supermarkets, hospitality venues and high-demand self-service environments. Thanks to ventilated cooling, automatic defrosting and LED lighting, products are always perfectly cooled and attractively displayed. The self-closing double glass door provides extra convenience and energy efficiency. Dimensions: 1955x720x2030 mm (WxDxH) – power 0.73 kW – capacity 1900 litres – temperature +2/+10°C – weight 350 kg.

Key features:

- **Ventilated cooling:** ensures a constant and even temperature distribution throughout the unit.
- **High capacity & robust design:** equipped with 5 heavy-duty shelves, each with a load capacity of up to 80 kg.
- **Self-closing double glass doors:** reduces cold loss and improves energy efficiency.
- **LED lighting:** energy-efficient and ideal for clear and attractive product presentation.
- **Energy-efficient design:** energy label B and insulated with 50 mm thick panels for optimal efficiency.

Whether you are displaying drinks, dairy or packaged goods – the Wall Mounted Unit Luke 1.9 delivers a reliable and professional solution for any retail environment. Order today and upgrade your product presentation!





EAN code	6153306187143	Width (mm)	1955
Depth (mm)	720	Height (mm)	2030
Material	Powder coated steel	Material interior	Powder coated steel
Color	Black	Gross Weight (kg)	350
Voltage (Volt)	230	Frequency (Hz)	50
Electrical power (kW)	0,73	Model tabletop/ freestanding/drop-in	Freestanding
Cooling agent	R 290	Temperature range (°C)	+2/+10
Max. grid load (kg)	80	Gross Capacity (Ltr)	1900
Dim. interior WxDxH (mm)	1885x600x1570	Grid(s) size WxD (mm)	936x450
Size plateau WxD (mm)	936x450	Double glass	Yes
Temperature display	Yes, digital	Lights	Yes, LED
Type of cooling	Ventilated	Lockable	No
Mobile	Yes	Lighting (Watt)	100
Number of doors	3	Number of levels	5
Noise level (dB)	60	Execution window	Straight
Defrost	Automatic	Max. ambient temperature (°C)	32
Insulation thickness (mm)	50	Energy Class (A/G)	B
Brand	COMBISTEEL	Refrigerant quantity (gr)	80
Cord length (mm)	2500	EPREL ID	2559404
Plug and play (EU plug)	Yes	Self-closing door	Yes
Taric Code	8418501990	Door left / right hinging	Left and right hinged
Parcel ready	No		



ENERG



Combisteel

7550.0115



2902 kWh/annum


4,20 m²


9°C
1°C

2019/2018

