

WALL MOUNTED UNIT LUKE 2.5

TRANSPORT ON REQUEST

€4,950.00

SKU:

7550.0120

Introducing the powerful Wall Mounted Unit Luke 2.5 – the ideal refrigeration solution for extra-large supermarkets and professional display environments!



The Wall Mounted Unit Luke 2.5 is a powerful and stylish refrigeration solution designed for maximum-capacity chilled product display. This freestanding black model is ideal for supermarkets, wholesalers and high-traffic self-service environments where large volumes need to be stored and presented efficiently. Thanks to ventilated cooling, automatic defrosting and LED lighting, products are always perfectly chilled and clearly visible. The self-closing double glass door ensures efficient operation and energy savings. Dimensions: 2508x720x2030 mm (WxDxH) – power 1.2 kW – capacity 2000 litres – temperature +2/+10°C – weight 380 kg.

Key features:

- **Ventilated cooling:** ensures stable and even temperature distribution throughout the cabinet.
- **Extra high capacity & robust design:** equipped with 5 heavy-duty shelves, each with a load capacity of up to 80 kg.
- **Self-closing double glass doors:** reduces cold loss and supports energy-efficient operation.
- **LED lighting:** energy-efficient and enhances product visibility and presentation.
- **Energy-efficient design:** energy label C and 50 mm thick insulation panels for reliable performance.

Whether you are displaying drinks, dairy or packaged goods – the Wall Mounted Unit Luke 2.5 delivers maximum capacity and a professional look for any retail environment. Order today and upgrade your product presentation!



EAN code	6153306221250	Width (mm)	2508
Depth (mm)	720	Height (mm)	2030
Material	Powder coated steel	Material interior	Powder coated steel
Color	Black	Gross Weight (kg)	380
Voltage (Volt)	230	Frequency (Hz)	50
Electrical power (kW)	1,2	Model tabletop/ freestanding/drop-in	Freestanding
Cooling agent	R 290	Temperature range (°C)	+2/+10
Max. grid load (kg)	80	Gross Capacity (Ltr)	2000
Dim. interior WxDxH (mm)	2448x600x1570	Size plateau WxD (mm)	1213x450
Operation	Digital	Double glass	Yes
Temperature display	Yes, digital	Lights	Yes, LED
Type of cooling	Ventilated	Lockable	No
Mobile	Yes	Lighting (Watt)	100
Number of doors	4	Number of levels	5
Noise level (dB)	60	Execution window	Straight
Defrost	Automatic	Max. ambient temperature (°C)	32
Insulation thickness (mm)	50	Energy Class (A/G)	C
Brand	COMBISTEEL	Refrigerant quantity (gr)	160
Cord length (mm)	2500	EPREL ID	2559411
Plug and play (EU plug)	Yes	Self-closing door	Yes
Taric Code	8418501990	Door left / right hinging	Left and right hinged
Parcel ready	No		



ENERG



Combisteel

7550.0120



4464 kWh/annum


5,20 m²


9°C
0°C

2019/2018

