

PROMO

Coffee machine 2 groups, automatic (with display) - **BLACK**

AROMA/2EB

Descriptions

mm (W x D x H)	750 x 600 x 595
kW	3.7
Voltage	230/1N 50-60Hz
gross Weight (Kg)	69 kg
Volume (m ³)	0.39 m ³

Page Catalog : **356-GOLD**Page Promo : **80-Pr24-25**

Product details

- Version for espresso coffee and American coffee (small lifting cup rest grill).
- Boiler capacity 11 litres.
- 2 steam valves, tube and head steaming all stainless steel
- 1 hot water outlet, electronic control, programmable.
- Supplied with 3 pouring spouts, 2x (2 cups) and 1x (1 cup) and "blind" filter for daily maintenance of the groups.
- Electronic machines with "volumetric" dosing unit, control keypad with backlit keys (double contact).
- Unit made of brass (chrome finish), heat guaranteed, with pre-infusion, solenoid valve for each unit.
- Automatic group cleaning program.
- Hot water outlet, for tea, herbal teas, etc... With quantity programming.
- Copper boiler, with heat exchanger for each group, double control probe to avoid dry heating, electric resistance heating, automatic water level control, visual alarm device (flashing keyboard keys).
- Anti-limestone magnet placed at the outlet of the heat exchanger of each group.
- Built-in motor pump.
- General On/Off switch, with indicator light and an analog manometer to display the pump pressure.
- Upper cup heater, equipped with ON/OFF switch, with removable antibacterial and machine washable mesh.

- Lower shelf with discharge, with removable upper grids, all made of stainless steel, easy to maintain.
- Body structure made of stainless steel and painted steel.
- 4 adjustable lower feet.
- The device is built in compliance with the current CE standards.

The +

The all-new electronic espresso coffee machines Aroma Line are equipped with a programmable microprocessor including:

A) Programming of coffee doses for each group.

B) Management of the automatic filling of the boiler.

C) Clock and date management.

D) Storage of "total" prepared coffees.

E) Management of the optimal boiler temperature by THERMOPID

F) Visual alarm for lack of water in the boiler.

G) Automatic hot water dosing.

H) Alarm for machine maintenance and water softener regeneration.

I) Self-cleaning program for coffee groups... etc.

J) Possibility of manual activation/deactivation of the ECO MODE function for a reduction in energy consumption (boiler temperature at 80°C).

K) Display of various alarms... etc Display with digital display: (5 languages: Italian, English, French, German, Spanish,).