



SOLID DOOR UPRIGHT REFRIGERATION

Description

Featuring high grade AISI 304 stainless steel exterior and interior the Inomak premium range is perfect for fresh meat storage and looks the part too! Available in both full and slim line depths along with a choice of custom RAL colours. Please note custom RAL colours are made to order therefore come with longer lead times.

All models come with self closing doors, replaceable door gasket, lock, 4 shelves per door and heavy duty castors as standard. The epoxy coated evaporator and low maintenance condenser allow for minimal maintenance work.



Features

- High grade AISI 304 stainless steel exterior & interior
- 4 x GN2/1 shelves per door
- Self closing door
- Replaceable door gasket
- Reversible door
- Lock as standard
- Heavy duty castors as standard (SL Single doors seperately)
- Epoxy coated evaporator to resist corrosion

MODEL	DOORS	SHELVES	GROSS CAPACITY	REFRIGERANT	TEMPERATURE RANGE	DIMENSIONS (mm)	ENERGY RATING	POWER USAGE	KWH/ANNUM	POWER	WEIGHT (kg)
CAP172	1	4	654L	R290	-2°C / +8°C	H2115 x W720 x D868	A+ D	615W	796	13amp	143
CBP172	1	4	654L	R290	-10°C / -22°C	H2115 x W720 x D868	A+ D	606W	2336	13amp	145
CEP2144	2	8	1432L	R290	-2°C / +8°C	H2115 x W1440 x D868	A+ E	836W	1898	13amp	222
CFP2144	2	8	1432L	R290	-10°C / -22°C	H2115 x W1440 x D868	A+ D	990W	4380	13amp	234
CAP172SL	1	4	560L	R290	-2°C / +8°C	H2115 x W720 x D768	A+ D	526W	693	13amp	135
CBP172SL	1	4	560L	R290	-10°C / -22°C	H2115 x W720 x D768	A+ D	598W	2044	13amp	144
CEP2144SL	2	8	1227L	R290	-2°C / +8°C	H2115 x W1440 x D768	A+ E	896W	1569	13amp	207
CFP2144SL	2	8	1227L	R290	-10°C / -22°C	H2115 x W1440 x D768	A+ D	797W	4124	13amp	212