



346 218 315 152

DB302S

Backbar Cooler

Product Features

- Double glazed tempered glass
- Ventilated cooling for fast pull-down and even temperature
- LED interior light
- Adjustable wire shelves
- Easy access electronic thermostat
- Automatic defrost
- Adjustable feet
- Lock

Backbar with three sliding doors

Designed for busy bars, restaurants and cafés, this budget-friendly backbar cooler combines reliable performance with an attractive presentation. The black exterior and anthracite interior create a contemporary look, while bright LED lighting enhances the visibility of the drinks inside.

Flexible wire shelves can be repositioned to accommodate everything from cans to taller bottles. Their plastic-coated finish helps simplify cleaning and maintenance, making day-to-day operation easier for staff.

The ventilated cooling system quickly restores the set temperature after restocking and maintains an even temperature throughout the cabinet. An accessible electronic thermostat allows temperatures to be monitored and adjusted with ease.

Built for everyday commercial use, this backbar cooler is easy to operate, straightforward to clean and ideal for keeping service running efficiently during busy periods.

Measures and Content

Gross / Net Weight	kg	95 / 88
Net Volume	l	288
Gross Volume	l	339
Gross / Net Volume	l	339 / 288
Total Display Area	m²	0.239
Temperature Range	°C	+2 to +10
Climate Class		4

Design and Material

Exterior Finish		Black RAL9005
Interior Finish		Grey RAL7037
No. of Doors		3
Door Number & Type		3
No. of Shelves	pcs	6
Shelves Number & Type		6 wire shelves grey
Shelf Color		Grey
Shelf Dimensions		395x320 mm
Max load on Shelves	kg/m²	230
Feet / Legs		4 adjustable feet
Lock		Yes
Interior Light		LED
Tempered glass		Yes

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant Charge	g	50
Refrigerant		R600a
Thermometer		Yes

Power and Consumption

Type of refrigeration		Supermarket cabinet
Energy Class		D
Annual Energy Consumption	kWh/year	674.885
Energy Consumption	kWh/h	0.077
Energy Consumption	kWh/24h	1.849
EEL	%	43.7
Input Power	W	205
Voltage / Frequency	V/Hz	220-240/50

Dimensions

External Dimension (WxDxH)	mm	1350 x 526 x 870
Internal Dimension (WxDxH)	mm	1265 x 418 x 720
Packed Dimension (WxDxH)	mm	1435 x 575 x 940
40ft Container Load	pcs	64



Protective thermostat
cover

Lock