WEIGHT ONLY OR
PRICE COMPUTING SCALE

CHECKOUT SCALE

DPOS-400 series



Dimensions

DATA IN mm

A	50
B	275
C	65
D	345
E	420
F	45




Plate dimensions: L300 x W230 mm.
Weight with packaging: 5.0 kg.

LCD GRAPHIC DISPLAY

RS-232

USB

METROLOGICAL VERIFICATION OPTIONAL (EU)

Models

Flat Format

	Vendor Display	Buyer Display	Communication protocols	Power	Capacity / Accuracy	Reference
DPOS-400 F – 1 DISP.	LCD Graphic	-	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POSP00LNE_ _
DPOS-400 F – 2 DISP.	LCD Graphic	LCD Graphic	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POSPP0LNE_ _

Pole Format

	Vendor Display	Buyer Display	Communication protocols	Power	Capacity / Accuracy	Reference
DPOS-400 P– 1 DISP.	LCD Graphic	-	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POST00LNE_ _
DPOS-400 P – 2 DISP.	LCD Graphic	LCD Graphic	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POSTT0LNE_ _
DPOS-400 P – 2 DISP. (1 in base and 1 in pole)	LCD Graphic	LCD Graphic	Up to 100	USB	6 kg / 2 g - 15 kg / 5 g	7POSPT0LNE_ _

(M) optional

Characteristics and functionality

Main characteristics

- Weight only or price computing scale for checkout applications.
- Modular and modern design.
- Easy integration into counters.
- Valid for legal metrology.

Features

- Tare, fix tare and manual zero.
- Display of price in a secondary currency.
- Energy saving via programmable on and off back lighting switching and automatic disconnection.
- Power supply and communications through one single USB cable.

Capacity / Accuracy

- Multi-range (3,000 divisions): 6 kg / 2 g - 15 kg / 5 g.
- Optional:
  > Mono-range (3,000 divisions): 15 kg / 5 g.

Available formats

- Flat.
- Pole.

Construction

- Structure:
  > ABS plastic casing.
- Displays:
  > Easy to install in multiple positions (1 or 2 displays).
  > Backlit LCD matrix graphic display.
  > 5 digits (up to H20 mm) per display.
  > Shows only weight or weight, price/kg and total (connected to POS and depending on the communication protocol).
- Keypad with 3-keys.
- Plate:
  > Type: Flat.
  > Material: Stainless steel.

Communication to PC / POS / ECR

- USB and RS-232 interfaces.
- Communication protocols available for the main POS and ECR in the market.
- Multi-protocol: communication protocol is selected in the scale (more than 50 protocols available).

Power supply

- Power via USB connection from a PC, POS, ECR, etc.

Energy consumption

- 1 W (approx.).

Options

Option	Characteristics	Ref.
Capacity 15 kg / 5 g	Mono-range (3,000 divisions).	...N_ _ (*)
Metrological verification (M)	According to EU weighing directives. (See section on equipment metrological verification).	Consult

(*) The scale references with this capacity are obtained by replacing the last characters of the reference for the standard scale with the indicated ending.

Note:
- The references correspond to standard models: black ABS plastic casing, backlit LCD segment display, flat stainless steel plate and RS-232 and USB communications. Capacity/Accuracy: 6 kg / 2 g - 15 kg / 5 g.