



EM300

Upright Back Bar

Product Features

- Fully automatic
- Fan assisted cooling
- Lock
- Adjustable shelves
- Adjustable feet
- LED interior light with switch
- Digital controller and temperature display
- Replaceable door gasket
- Door not reversible

Ideal for the pub or bar that wants to increase display capacity of chilled bottled drinks and cans while keeping the refrigeration footprint as low as possible. The EM upright range of back bar coolers come in single or double door options. Vertical LED interior lighting helps to illuminate the product and create an attractive display. The fan assisted refrigeration system ensures even and rapid cooling over the whole cabinet and an energy efficient refrigeration system helps keep running costs low.

Measures and Content

| | | |
|--------------------|----------------|----------|
| Total Display Area | m ² | 0.6 |
| Temperature Range | °C | +2 to +8 |
| Climate Class | | 4 |
| Gross / Net Weight | kg | 114 / 98 |
| Gross Volume | l | 307 |
| Gross / Net Volume | l | 307 / |

Design and Material

| | |
|-----------------------|---------------------|
| No. of Doors | 1 |
| Door Number & Type | 1 hinged glass door |
| Max load on Shelves | kg/m ² |
| No. of Shelves | pcs |
| Shelves Number & Type | 4 wire shelves |
| Tempered glass | Yes |
| Exterior Finish | Black |
| Interior Finish | Hammered Aluminium |

Cooling and Functions

| | |
|--------------------|---------------------|
| Type of Defrost | Automatic, electric |
| Refrigerant | R600a |
| Refrigerant Charge | g |
| Thermometer | Yes |

Power and Consumption

| | |
|---------------------------|----------------|
| Energy Class | B |
| Max Ambient | 30°C at 55% RH |
| Energy Consumption | kWh/24h |
| Annual Energy Consumption | kWh/year |
| EEI | % |
| Power | 13 Amp |
| Input Power | W |
| Voltage / Frequency | V/Hz |
| Noise Level | dB(A) |

Dimensions

| | | |
|----------------------------|-----|---------------------|
| Internal Dimension (WxDxH) | mm | 535 x 424 x 1437 |
| External Dimension (WxDxH) | mm | 600 x 520 x 1872 |
| Packed Dimension (WxDxH) | mm | 655 x 570 x 2028 mm |
| 40ft Container Load | pcs | 71 |



Digital controller



Adjustable shelves