



FSC1380

Glass Door Merchandiser

Product Features

- Fully automatic
- Fan assisted cooling
- Lock
- Adjustable shelves
- Adjustable feet
- LED interior light with switch
- Thermometer
- Light canopy with switch
- Replaceable door gasket

The FSC1380 takes the quality and reliability of the FS1380 and adds a light canopy making it ideal for branding. Full length vertical LED lighting in the door frame illuminates the product in the cabinet from the front to produce an attractive display. The cabinet comes with fan assisted cooling and lock fitted as standard.

Measures and Content

| | | |
|--------------------|----|-----------|
| Temperature Range | °C | +2 to +10 |
| Climate Class | | 4 |
| Gross / Net Weight | kg | 87 / 82 |
| Gross Volume | l | 372 |
| Net Volume | l | 347 |
| Gross / Net Volume | l | 372 / 347 |

Design and Material

| | | |
|-----------------------|-------|----------------------|
| No. of Doors | | 1 |
| Door Number & Type | | 1 hinged glass door |
| Max load on Shelves | kg/m² | 196 |
| No. of Shelves | pcs | 5 |
| Shelf Color | | White |
| Shelf Dimensions | | 498 x 405 mm |
| Shelves Number & Type | | 5 wire shelves white |
| Tempered glass | | Yes |
| Canopy Light | | LED Cold White |
| Canopy Type | | D-Shape |
| Feet / Legs | | 2 adjustable feet |
| Castors | | 2 rollers |
| Exterior Finish | | White |
| Interior Finish | | White |
| Interior Light | | LED |
| Lock | | Yes |

Cooling and Functions

| | | |
|--------------------|---|-----------------------|
| Type of Controller | | Mechanical |
| Type of Cooling | | Fan assisted |
| Type of Defrost | | Automatic / Off Cycle |
| Refrigerant | | R600a |
| Refrigerant Charge | g | 80 |
| Thermometer | | Yes |

Power and Consumption

| | | |
|---------------------------|----------|----------------|
| Energy Class | | D |
| Max Ambient | | 30°C at 55% RH |
| Energy Consumption | kWh/24h | 2.25 |
| Annual Energy Consumption | kWh/year | 821 |
| EEl | % | 49.7 |
| Power | | 13 Amp |
| Input Power | W | 295 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 45 |

Dimensions

| | | |
|----------------------------|-----|---------------------|
| Internal Dimension (WxDxH) | mm | 470 x 440 x 1555 |
| External Dimension (WxDxH) | mm | 595 x 640 x 1980 |
| Packed Dimension (WxDxH) | mm | 680 x 710 x 2080 mm |
| 40ft Container Load | pcs | 54 |



Strong handle



Lock