



LGC5000 Black

Glass Door Merchandiser

Product Features

- Fully automatic
- Fan assisted cooling
- Automatic defrost
- Lock
- Adjustable shelves
- Castors and locking feet
- LED interior light with switch (2 LED strips per door)
- Digital controller and temperature display
- LED Light canopy with switch
- Internal stainless steel base
- Self closing doors with stay open feature for ease of loading

Elegant display chiller with canopy

The TEFCOLD LGC5000 chiller now available in a sleek black finish. This exciting update allows the unit to seamlessly blend into various retail and catering environments, making it an excellent choice for establishments seeking a sophisticated and high-quality aesthetic. Each door boasts two vertical LED light strips, these draw attention to the product on display giving a striking contrast against the black interior of the cabinet. There is also an LED light canopy which is ideal for branding and advertising. The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. Additionally, the carefully engineered refrigeration system is highly energy-efficient, minimising operational costs while keeping your products at their optimal temperature. The unit is also fitted with castors, to allow moving for cleaning purposes and other necessary adjustments.

Measures and Content		
Total Display Area	m ²	1.38
Temperature Range	°C	+1 to +8
Climate Class		4
Gross / Net Weight	kg	210 / 190
Gross Volume	l	1108
Net Volume	l	922
Gross / Net Volume	l	1108 / 922
Design and Material		
No. of Doors		2
Door Number & Type	2 hinged glass doors	
Max load on Shelves	kg/m ²	196
No. of Shelves	pcs	10
Shelf Dimensions	618*622	
Shelves Number & Type	10	
Tempered glass	Yes	
Exterior Finish	Black	
Interior Finish	Black	
Interior Light	2 x Vertically LED in door frame	
Cooling and Functions		
Type of Defrost	Automatic / Off Cycle	
Refrigerant	R290	
Refrigerant Charge	g	120
Thermometer	Yes	
Power and Consumption		
Energy Class	B	
Max Ambient	30°C at 55% RH	
Energy Consumption	kWh/24h	5.21
Annual Energy Consumption	kWh/year	1900
EEI	%	19
Power	13 Amp	
Input Power	W	400
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	58
Dimensions		
Internal Dimension (WxDxH)	mm	1262 x 640 x 1520
External Dimension (WxDxH)	mm	1382 x 805 x 2065
Packed Dimension (WxDxH)	mm	1430 x 860 x 2260 mm
40ft Container Load	pcs	22



Illuminated canopy



Strong castors